

Features

Dual backlit LCD digital display of moisture & temperature
 Readings with Integral electro Pins
 User selectable Wood moisture, Building material moisture, °C, °F
 Auto power off

Specifications

Electrode length	8 mm
Measuring range	Wood: 6 – 44% Building material: 0.2– 2.0% Ambient temperature: 0 to 50°C (32 to 122°F)
Accuracy	Wood: ±2 % materials: ±0.2%
Ambient temperature	±1°C / ±1.8°F
Auto power OFF	After approx. 3 minutes
Operation temperature	0 - 40°C
Ambient Relative humidity	0 – 85 %RH

Size(HxWxD): 96mm x 40mm x 20mm **Accessories :**

Weight: 83g 4xLR44 button batteries, gift box and carrying case



Model 120

DT-125H/125G Moisture Meters

125H/125G series moisture meters are used for testing moisture in wood, plaster and building materials. Integrated characteristics for 8 material groups increase the accuracy of measurements. The wet/dry indicator evaluates and interprets measurements with respect to the given material. The clearly organised, functional display and rubber guard around the housing make this unit well-suited for use in the rough professional environment.

125G can meet with different measuring requirements with various professional remote probes.

Features

Large LCD display
 Readings with Moisture Probe or Hammer Electrode
 Readings with Integral electro Pins

Specifications

Model	125H	125G
Electrode length	8 mm	
Electrodes	Integrated, replaceable	
Measuring range Wood:	1 – 75 %	
Measuring range	Wood: 1 – 75 % Building material: 0.1– 2.4 % Ambient temperature: -40 to 70°C (-40 to 158°F) Ambient Relative Humidity: 0 to 100%	
Accuracy	Wood: 0...30% / ±1 % 30...60% / ±2% 60...75% / ±4% Other materials: / ±0.5%	
Ambient temperature range	-40 °C~ -10°C and +40 ~ +70°C / ±2°C -10 °C~ +40°C / ±1°C	
Ambient Relative Humidity	0~20% and 80 ~ 100% / ±5.0% 20~ 80%/±3.5%	
Auto power OFF	After approx. 3 minutes	
Auto LCD backlight OFF	After approx 10 seconds	
Housing material	Impact-proof plastic housing	
Operation temperature	0 - 40°C	
Ambient Relative humidity	0 – 85 %RH	
Professional remote probes	No	Yes

Size(HxWxD): 160mm x 60mm x 28mm

Weight: 203g

Accessories :

3xCR2032 button batteries, Moisture Hammer Probe, Moisture Baseboard Probe, Moisture Probe Extenders, gift box and carrying case (125G)
 3 x CR2032 button batteries (125H)



Model 125G



EMC
 EN: 61326