

DT-926A/926B/926/926H/927A/927/927H/928BT

Compact True RMS Multimeter with Battery test

CEM



Bluetooth
Meterbox Pro

• Double molded plastic housing

• True RMS

927 compa 600V True RMS 13-function auto-ranging multimeter with built-in NCV and Live detector.

926 is durable and attractive 600V multimeter for the beginning electrician. 7 Measurement functions including AC and DC voltage, DC current, resistance, diode test, battery test, and continuity provide the capability to tackle any basic electrical task.

	GOOD	LOW	BAD
1.5V	>1.3V	0.95 to 1.3V	<0.95V
9V	>7.7V	5.7 to 7.7V	<5.7V



EMC & LVD

EN: 61326


EN: 61010-1

EN: 61010-02-032

EN: 61010-02-033



Model 926H



Model 927



Meterbox Pro

Model 928BT

Features

	926A	926B	926	926H	927A	927	927H	928BT
Digital display counts with backlit	2000	2000	2000	6000	4000	4000	6000	6000
True RMS measurement	*		*	*	*	*	*	*
Range selection	Manual	Manual	Manual	Manual	Auto	Auto	Auto	Auto
MAX/MIN hold				*	*	*	*	*
0.1~99.9% Duty Cycle measurement						*	*	*
Diode & Continuity buzz check	*	*	*	*	*	*	*	*
Auto Power Off	*		*	*	*	*	*	*
Display backlight					*	*	*	*
Data Hold/REL measurement	*	*/-	*	*	*	*	*	*
Fast and accurate capacitance measurement						*		
Non-Contact ACV & ACV Live detection				*	NCV	*	*	*
Backlight for LCD, Knob Switch, Flashlight							*	*
1.5V and 9V battery test	*	*	*	*		*		
Full ranges protection	*	*	*	*	*	*	*	*
Drop tested up to 2 meters	*	*	*	*	*	*	*	*
Square wave signal output							*	*
Low input Impedance (around 3kΩ)							*	*
Bluetooth interface with Meterbox Pro software								*

Specifications

Function	Max Range	Basic Accuracy	926A	926B	926	926H	927A	927	927H	928BT
Voltage DC	600V	±0.5%	*	*	*	*	*	*	*	1000V
Voltage AC	600V	±1.2%	*	*	*	*	*	*	*	1000V
Current DC	10A	±1.5%	*	*	*	*	*	*	*	*
Current AC	10A	±2.0%	*				*	*	*	*
Resistance	2MΩ	±0.8%	*	*	*					
	40MΩ	±3.0%				60MΩ	*	*	60MΩ	60MΩ
Capacitance	100mF	±3.5%				60mF	4mF	*	*	*
Frequency	10MHz	±1.5%					*	*	10KHz	10KHz
Temperature	760°C/1400°F	±1.5%					*	*	*	*
Battery test	Test 1.5V and 9V batteries		*	*	*	*		*		
Diode Check			*	*	*	*	*	*	*	*
Continuity Test			*	*	*	*	*	*	*	*

Size(HxWxD): 151mm x 75mm x 45mm Weight: 255g

Accessories: Test leads, 2x1.5V batteries and type K temperature probe (927/927A/927H/928BT), clamshell.