

Professional 1000A AC, AC/DC True RMS Clamp Meters with TFT color LCD display



CE

EMC & LVD
EN: 61326
EN: 61010-1
EN: 61010-02-032
EN: 61010-02-033



The 9380/9381/9382 series clamp meters provide fast A/D converting sampling time, high accuracy, offer all needed features for measurement. They are with modern bodies and jaws design for perfect handheld and tight place testing. A large backlit display is easy to see and a handy data hold keeps measurements on the display.

- Double molded plastic housing
- True RMS measurement for ACV & ACA
- Flexible current probe expands the measurement range to 3000 ACA (9382)

Features

	9380	9380A	9381	9381A	9382	9382B
Current measurement	AC	AC	AC/DC	AC/DC	AC/DC	AC/DC
Display counts	4000	6000	4000	6000	6000	6000
1.8" TFT color LCD display counts					*	Negativity
AC True RMS	*	*	*	*	*	*
Data Hold & Peak Hold		*		*	*	*
Max /Min Hold	*		*		*	*
REL (Zero) Function			*	*	*	*
Flashlight and Backlight	*	*	*	*	Flashlight	Flashlight
Auto Power Off	*	*	*	*	*	*
Low battery indication	*	*	*	*	*	*
100ms Inrush current		*		*	*	*
Low input impedance prevents false readings due to "ghost voltage" (LoZ)		*		*	*	
Low pass filter for accurate measurement of variable frequency drive (VFD) signals		*		*	*	*
Max Jaw opening 1.4" (35mm)	*	*	*	*	*	*
Bluetooth interface					*	*
3000A ACA flexible clamp					*	
Trend capture function					*	
Fast response time					10 times/sec.	
100 Graph Data review					*	
NCV Function	*	*	*	*	*	*

Specifications

Function	Max Range	Basic Accuracy	9380	9380A	9381	9381A	9382	9382B
Voltage DC	1000V	$\pm(0.5\%+2d)$	*	*	*	*	*	*
Voltage AC	1000V	$\pm(1.0\%+5d)$	*	*	*	*	*	*
Current DC	1000A	$\pm(2.0\%+5d)$			*	*	*	*
Current AC	1000A	$\pm(2.5\%+8d)$	*	*	*	*	*	*
ACA flexible	3000A	$\pm(2.5\%+8d)$					*	
Resistance	60M Ω	$\pm(3.0\%+5d)$	40M Ω	*	40M Ω	*	*	*
Temperature	1000°C/1832°F	$\pm(1.0\%+3d)$	*	*	*	*	*	*
Capacitance	100mF	$\pm(2.5\%+5d)$	*	*	*	*	*	*
Frequency	10kHz	$\pm(0.5\%+2d)$	*	*	*	*	*	*
Inrush Current	1000A	$\pm(2.5\%+2d)$		*		*	*	*
Continuity check	Buzzer sounds at 50 Ω							
Diode test	Test current 0.3mA							

Size(HxWxD): 250mm x 78mm x 40mm Weight: 350g

Accessories: Test leads, gift box with carrying case, Temperature probe and 1.5V AAA x 3 batteries, Software(9382) Flexible clamp (9382)




- Fast response time
- True RMS

- TFT color LCD display (9382)
- PC Calibration



Flexible clamp (optional)
Model DT-320BS



Meterbox Pro



Model 9382



Model 9381



Model 9380